



## Dahua Technology Lite DH-HAC-PT1239AN-A-LED cámara de vigilancia Torreta Cámara de seguridad CCTV Exterior 1920 x 1080 Pixeles Techo/pared

**Marca :** Dahua Technology

**Familia de productos:** Lite

**Código del producto:** DH-HAC-PT1239AN-A-LED

**Nombre del producto :** DH-HAC-PT1239AN-A-LED

Camara PT de 2 Megapixeles HDCVI/ Full Color/ Lente de 2.8 mm/ 106 Grados de Apertura/ Microfono Integrado/ 40 Metros de Iluminación LED/ Super Adapt/ WDR Real de 130 dB/ IP66/ #LoNuevo Dahua Technology Lite DH-HAC-PT1239AN-A-LED. Tipo: Cámara de seguridad CCTV, Colocación compatible: Exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared, Color del producto: Blanco, Factor de forma: Torreta. Ángulo de rotación: 355°, Ángulo de visión del objetivo, horizontal: 106°, Ángulo de visión del objetivo, vertical: 56°. Tipo de sensor: CMOS. Distancia focal fija: 2.8 mm, Distancia de detección (angular): 43.9 m, Distancia de observación (angular): 17.5 m

Performance		Night vision	
Type *	CCTV security camera	Night vision distance	40 m
Placement supported *	Outdoor	LED type	White
Connectivity technology *	Wired	Number of illumination LEDs	1
Wide Dynamic Range (WDR)	✓	Video	
Day/night mode	✓	Maximum resolution *	1920 x 1080 pixels
Built-in light	✓	Total megapixels *	2 MP
Dynamic range	130 dB	Supported graphics resolutions	960 x 480, 960 x 576, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080)
Certification	CE-LVD: EN 62368-1; CE-EMC: EN 55032; EN 55035	Frame rate	30 fps
Design		Noise reduction	✓
Form factor *	Turret	Noise reduction technology	2D noise reduction
Mounting type *	Ceiling/wall	Gain control type	Auto/Manual
Product colour *	White	Privacy masking	✓
Housing material	Plastic	Back Light Compensation (BLC)	✓
International Protection (IP) code	IP66	Highlight Compensation (HLC)	✓
Camera		Network	
Camera pan control	✓	Ethernet LAN *	✗
Camera tilt control	✓	Wi-Fi *	✗
Minimum illumination	0 lx	Bluetooth *	✗
Angle of rotation	355°	Storage	
Lens viewing angle, horizontal	106°	Built-in HDD *	✗
Lens viewing angle, vertical	56°	Ports & interfaces	
Lens viewing angle, diagonal	355°	BNC output ports	1
Tilt angle range	0 - 90°	Security	
Pan range	0 - 355°	Mirror	✓
White balance	Auto, Manual	Power	
Camera shutter type	Electronic	Power source type *	DC
Camera shutter speed	1/25 (1/30) - 1/1000000 s	Power consumption (max)	3.1 W
Image sensor		DC output voltage	12
Number of sensors	1	Operational conditions	
Progressive scan	✓	Operating temperature (T-T)	-40 - 60 °C
Sensor type *	CMOS	Storage temperature (T-T)	-40 - 60 °C
Lens system		Operating relative humidity (H-H)	0 - 95%
Number of lenses *	1	Storage relative humidity (H-H)	0 - 95%
Maximum aperture number	1.6		
Fixed focal length	2.8 mm		
Detect distance (wide)	43.9 m		

Lens system		Weight & dimensions	
Observe distance (wide)	17.5 m	Height	92.9 mm
Recognize distance (wide)	8.8 m	Diameter	9.13 cm
Identify distance (wide)	4.4 m	Weight	380 g
Closest focusing distance	0.7 m	Packaging data	
Night vision		Package weight	620 g
Night vision *	✓	Packaging content	
		Number of cameras *	1

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date